Apple Inc.



Apple OS X CoreCrypto Kernel Module, v5.0 FIPS 140-2 Non-Proprietary Security Policy

Prepared for:
Apple Inc.
1 Infinite Loop
Cupertino, CA 95014
www.apple.com

Prepared by: atsec information security Corp. 9130 Jollyville Road, Suite 260 Austin, TX 78759 www.atsec.com

Table of Contents

| 1 | INT | RODUCTION | 4 |
|----|---|---|--|
| | 1.1 | Purpose | |
| | 1.2 | DOCUMENT ORGANIZATION / COPYRIGHT | |
| | 1.3 | EXTERNAL RESOURCES / REFERENCES | |
| | 1.3. | • | |
| | 1.4 | ACRONYMS | |
| 2 | CRY | PTOGRAPHIC MODULE SPECIFICATION | |
| | 2.1 | Module Description | - |
| | 2.1. | | |
| | 2.1. | | |
| | 2.1. | , | |
| | 2.2 | MODES OF OPERATION | |
| | 2.3 | CRYPTOGRAPHIC MODULE BOUNDARY | |
| | 2.4 | MODULE USAGE CONSIDERATIONS | |
| _ | CDV | | |
| 3 | | PTOGRAPHIC MODULE PORTS AND INTERFACES | |
| 4 | ROL | ES, SERVICES AND AUTHENTICATION | 18 |
| | 4.1 | ROLES | 18 |
| | 4.2 | Services | |
| | 4.3 | OPERATOR AUTHENTICATION | 23 |
| 5 | PHY | SICAL SECURITY | 24 |
| 6 | OPE | RATIONAL ENVIRONMENT | 25 |
| | 6.1 | Applicability | 25 |
| | 6.2 | POLICY | |
| 7 | CRY | PTOGRAPHIC KEY MANAGEMENT | 26 |
| | 7.1 | RANDOM NUMBER GENERATION | |
| | 7.1 | KEY / CSP GENERATION | |
| | 7.2 | KEY / CSP ESTABLISHMENT | |
| | 7.3 7.4 | KEY / CSP ENTRY AND OUTPUT | |
| | 7.5 | KEY / CSP STORAGE | |
| | 7.6 | KEY / CSP ZEROIZATION | |
| Q | | CTROMAGNETIC INTERFERENCE/ELECTROMAGNETIC COMPATIBILITY (EMI/EMC) | |
| | | -TESTS | |
| 9 | | | |
| | 9.1 | Power-Up Tests | |
| | | | |
| | 9.1. | 1 Cryptographic Algorithm Tests | 29 |
| | 9.1. | 1 Cryptographic Algorithm Tests | 29 |
| | 9.1. 9.1. | 1 Cryptographic Algorithm Tests | 29 29 |
| | 9.1. 9.1. 9.2 | 1 Cryptographic Algorithm Tests | |
| | 9.1. 9.1. 9.2 9.2. | 1 Cryptographic Algorithm Tests | |
| | 9.1. 9.1. 9.2 9.2. 9.2. | 1 Cryptographic Algorithm Tests | |
| | 9.1. 9.1. 9.2 9.2. 9.2. 9.2. | 1 Cryptographic Algorithm Tests | 29 29 29 29 30 30 |
| | 9.1. 9.1. 9.2 9.2. 9.2. 9.2. | 1 Cryptographic Algorithm Tests | |
| 10 | 9.1. 9.1. 9.2 9.2. 9.2. 9.2. 9.2. | 1 Cryptographic Algorithm Tests | |
| 10 | 9.1. 9.1. 9.2 9.2. 9.2. 9.2. 9.2. | 1 Cryptographic Algorithm Tests | |
| 10 | 9.1. 9.1. 9.2 9.2. 9.2. 9.2. 9.2. | 1 Cryptographic Algorithm Tests | 29 29 29 30 30 30 30 30 |
| 10 | 9.1. 9.1. 9.2 9.2. 9.2. 9.2. 9.2. | 1 Cryptographic Algorithm Tests | 29 29 29 30 30 30 31 31 32 32 33 |
| 10 | 9.1. 9.2 9.2. 9.2. 9.2. 9.2. 10.1 | 1 Cryptographic Algorithm Tests | 29 29 29 30 30 30 31 31 32 32 33 33 |

| 10.4.2 User Guidance | 31 |
|---|----|
| 11 MITIGATION OF OTHER ATTACKS | 32 |
| List of Tables | |
| Table 1: Module Validation Level | |
| TABLE 2: TESTED PLATFORMS | 8 |
| TABLE 3: APPROVED SECURITY FUNCTIONS | |
| TABLE 4: NON-APPROVED FUNCTIONS | 12 |
| TABLE 5: ROLES | 18 |
| TABLE 6: APPROVED AND ALLOWED SERVICES IN APPROVED MODE | |
| TABLE 6B: NON-APPROVED SERVICES IN NON-APPROVED MODE | 21 |
| TABLE 7: CRYPTOGRAPHIC ALGORITHM TESTS | 29 |
| | |
| List of Figures | |
| FIGURE 1: LOGICAL BLOCK DIAGRAM | 15 |

1 Introduction

1.1 Purpose

This document is a non-proprietary Security Policy for the Apple OS X CoreCrypto Kernel Module, v5.0. It describes the module and the FIPS 140-2 cryptographic services it provides. This document also defines the FIPS 140-2 security rules for operating the module.

This document was prepared in fulfillment of the FIPS 140-2 requirements for cryptographic modules and is intended for security officers, developers, system administrators, and end-users.

FIPS 140-2 details the requirements of the Governments of the U.S. and Canada for cryptographic modules, aimed at the objective of protecting sensitive but unclassified information.

For more information on the FIPS 140-2 standard and validation program please refer to the NIST website at http://csrc.nist.gov/cryptval.

Throughout the document "Apple OS X CoreCrypto Kernel Module, v5.0.", "cryptographic module", "CoreCrypto KEXT" or "the module" are used interchangeably to refer to the Apple OS X CoreCrypto Kernel Module, v5.0.

1.2 Document Organization / Copyright

This non-proprietary Security Policy document may be reproduced and distributed only in its original entirety without any revision, ©2015 Apple Inc.

1.3 External Resources / References

The Apple website (http://www.apple.com) contains information on the full line of products from Apple Inc. For a detailed overview of the operating system OS X and its security properties refer to [OS X] and [SEC]. For details on OS X releases with their corresponding validated modules and Crypto Officer Role Guides refer to the Apple Knowledge Base Article HT201159 - "OS X:Security certifications and validations" (https://support.apple.com/en-us/HT201159)

The Cryptographic Module Validation Program website (http://csrc.nist.gov/groups/STM/cmvp/index.html) contains links to the FIPS 140-2 certificate and Apple, Inc. contact information.

1.3.1 Additional References

- FIPS 140-2 Federal Information Processing Standards Publication, "FIPS PUB 140-2 Security Requirements for Cryptographic Modules," Issued May-25-2001, Effective 15-Nov-2001, Location: http://csrc.nist.gov/groups/STM/cmvp/standards.html
- FIPS 180-4 Federal Information Processing Standards Publication 180-4, March 2012, Secure Hash Standard (SHS)
- FIPS 197 Federal Information Processing Standards Publication 197, November 26, 2001 Announcing the ADVANCED ENCRYPTION STANDARD (AES)
- PKCS7 RSA Laboratories, "PKCS#7 v1.5: Cryptographic Message Syntax Standard," 1993. Location: http://www.rsa.com/rsalabs/node.asp?id=2129
- PKCS3 RSA Laboratories, "PKCS#3 v1.4: Diffie-Hellman Key Agreement Standard," 1993. Location: http://www.rsa.com/rsalabs/node.asp?id=2126
- IG NIST, "Implementation Guidance for FIPS PUB 140-2 and the Cryptographic Module Validation Program," March 2, 2015

Location: http://csrc.nist.gov/groups/STM/cmvp/standards.html

OS X OS X Technical Overview

Location:

https://developer.apple.com/library/mac/#documentation/MacOSX/Conceptual/OSX_T

echnology_Overview/About/About.html

SEC Security Overview

Location:

https://developer.apple.com/library/mac/navigation/#section=Topics&topic=Security

SP800-57P1 NIST Special Publication 800-57, "Recommendation for Key Management – Part 1:

General (Revised)," March 2007

SP 800-90A NIST Special Publication 800-90A, "Recommendation for Random Number

Generation Using Deterministic Random Bit Generators (Revised)," January 2012

UG User Guide

Location: https://developer.apple.com/library/mac/navigation/

1.4 Acronyms

Acronyms found in this document are defined as follows:

AES Advanced Encryption Standard

BS Block Size

CAVP Cryptographic Algorithm Validation Program

CBC Cipher Block Chaining mode of operation

CFB Cipher Feedback mode of operation

CMVP Cryptographic Module Validation Program

CSP Critical Security Parameter
CTR Counter mode of operation
DES Data Encryption Standard

DH Diffie-Hellman

DMA Direct Memory Access

DRBG Deterministic Random Bit Generator

DS Digest Size

ECB Electronic Codebook mode of operation

ECC Elliptic Curve Cryptography
EC Diffie-Hellman Diffie-Hellman based on ECC

ECDSA DSA based on ECC

E/D Encrypt/Decrypt

EMC Electromagnetic Co

EMC Electromagnetic Compatibility
EMI Electromagnetic Interference

FIPS Federal Information Processing Standard

FIPS PUB FIPS Publication

GCM Galois/Counter Mode

HMAC Hash-Based Message Authentication Code

HW Hardware

IPCU iPhone Configuration Utility

KAT Known Answer Test
KEK Key Encryption Key
KEXT Kernel extension

KDF Key Derivation Function

KO 1 Triple-DES Keying Option 1: All three keys are independent

KPI Kernel Programming Interface

KS Key Size (Length)

MAC Message Authentication Code

NIST National Institute of Standards and Technology

OFB Output Feedback (mode of operation)

OS Operating System

PBKDF Password-based Key Derivation Function

PWCT Pair Wise Consistency Test
RNG Random Number Generator

SHS Secure Hash Standard

SW Software

Triple-DES Triple Data Encryption Standard

TLS Transport Layer Security

2 Cryptographic Module Specification

2.1 Module Description

The Apple OS X CoreCrypto Kernel Module, v5.0 is a software cryptographic module running on a multi-chip standalone general-purpose computer.

The cryptographic services provided by the module are:

- Data encryption / decryption
- Generation of hash values
- Message authentication
- Signature generation / verification
- Random number generation
- Key derivation
- Key generation

2.1.1 Module Validation Level

The module is intended to meet requirements of FIPS 140-2 security level 1 overall. The following table shows the security level for each of the eleven requirement areas of the validation.

| FIPS 140-2 Security Requirement Area | Security Level |
|---|----------------|
| Cryptographic Module Specification | 1 |
| Cryptographic Module Ports and Interfaces | 1 |
| Roles, Services and Authentication | 1 |
| Finite State Model | 1 |
| Physical Security | N/A |
| Operational Environment | 1 |
| Cryptographic Key Management | 1 |
| EMI/EMC | 1 |
| Self-Tests | 1 |
| Design Assurance | 1 |
| Mitigation of Other Attacks | 1 |

Table 1: Module Validation Level

2.1.2 Module components

In the following sections the components of the Apple OS X CoreCrypto Kernel Module, v5.0 are listed in detail. There are no components excluded from the validation testing.

2.1.2.1 Software components

CoreCrypto has a KPI layer that provides consistent interfaces to the supported algorithms. These implementations include proprietary optimizations of algorithms that are fitted into the CoreCrypto framework.

The CoreCrypto KEXT is linked dynamically into the OS X kernel.

2.1.2.2 Hardware components

There is hardware acceleration for AES-NI within the cryptographic module boundary.

2.1.3 Tested Platforms

The module has been tested on the following platforms with and without AES-NI:

| Manufacturer | Model | Operating System |
|--------------|----------------------|------------------|
| Apple Inc. | Mac mini with i5 CPU | OS X 10.10 |
| Apple Inc. | iMac with i7 CPU | OS X 10.10 |
| Apple Inc. | MacPro with Xeon CPU | OS X 10.10 |
| Apple Inc. | MacBook with Core M | OS X 10.10 |

OS X 10.10 refers to OS X Yosemite v10.10

Table 2: Tested Platforms

2.2 Modes of operation

The Apple OS X CoreCrypto Kernel Module, v5.0 has an Approved and Non-Approved Mode of operation. The Approved Mode of operation is configured in the system by default and cannot be changed. If the device starts up successfully then CoreCrypto KEXT has passed all self-tests and is operating in the Approved Mode. Any calls to the Non-Approved security functions listed in Table 4 will cause the module to assume the Non-Approved Mode of operation.

The module transitions back into FIPS mode immediately when invoking one of the approved ciphers as all keys and Critical Security Parameters (CSP) handled by the module are ephemeral and there are no keys and CSPs shared between any functions. A re-invocation of the self-tests or integrity tests is not required.

Even when using this FIPS 140-2 non-approved mode, the module configuration ensures that the self-tests are always performed during initialization time of the module.

The module contains multiple implementations of the same cipher as listed below. If multiple implementations of the same cipher are present, the module automatically selects which cipher is used based on internal heuristics. This includes the hardware-assisted AES implementation (AES-NI).

Approved security functions are listed in Table 3. Column four ("Val. No.") of Table 3 lists the validation numbers obtained from NIST based on the successful CAVP testing of the cryptographic algorithm implementations on the platforms referenced in Table 2

Refer to http://csrc.nist.gov/groups/STM/cavp/index.html for the current standards, test requirements, and special abbreviations used in the following table.

Approved Security Functions

| Cryptographic | Standards | Usage / Description | Val. No. | | | |
|---------------|--|--|-----------|-----------|-------------|------------------|
| Function | | | i5 CPU | i7 CPU | Xeon CPU | Core M CPU |
| Triple-DES | ANSIX9.52- 1998 FIPS 46-3 SP 800-67 SP 800-38A Appendix E | Encryption / decryption with all keys independent Block chaining modes: ECB, CBC | 1895 | 1896 | 1897 | 1921 |
| AES | FIPS 197 SP 800-38A SP 800-38 E | Generic-software implementation (non-optimized using LibTomCrypt): Encryption / decryption Key sizes: 128 bits, 192 bits, 256 bits for block chaining modes ECB, CBC | 3323 | 3324 | 3325 | 3385 |
| | | Optimized-software implementation: Encryption / decryption Key sizes: 128 bits, 192 bits, 256 bits for block chaining modes ECB, CBC | 3066 | 3067 | 3102 | 3382 |
| | | AES-NI hardware implementation with optimized software implementation of block chaining modes: Key sizes: 128 bits, 192 bits, 256 bits for block chaining modes ECB, CBC | 3068 | 3069 | 3070 | 3384 |

| Cryptographic | Standards | Usage / Description | iption Val. No. | | I. No. | |
|---------------|------------|---|-----------------|-----------|-------------|------------------|
| Function | | | i5 CPU | i7 CPU | Xeon CPU | Core M CPU |
| | | AES-NI hardware implementation with generic software implementation (nonoptimized) of block chaining modes: Key sizes: 128 bits, 192 bits, 256 bits for block chaining mode CBC | 3071 | 3072 | 3073 | 3383 |
| SHS | FIPS 180-4 | Generic-software implementation (non-optimized): SHA-1 (BYTE-only) SHA-224 (BYTE-only) SHA-256 (BYTE-only) SHA-384 (BYTE-only) SHA-512 (BYTE-only) | 2755 | 2756 | 2757 | 2804 |
| | | Optimized-software implementation using SSE: SHA-1 (BYTE-only) SHA-224 (BYTE-only) SHA-256 (BYTE-only) | 2586 | 2545 | 2546 | 2803 |
| | | Optimized-software implementation not using SSE: SHA-1 (BYTE-only) SHA-224 (BYTE-only) SHA-256 (BYTE-only) | 2585 | 2543 | 2544 | 2802 |
| | | Optimized-software implementation using AVX1: SHA-256(BYTE-only) 64 bit word size | 2579 | 2580 | 2581 | 2800 |

| Cryptographic | Standards | Usage / Description | Val. No. | | | |
|---------------|--------------------------|--|-----------|-----------|-------------|------------------|
| Function | | | i5 CPU | i7 CPU | Xeon CPU | Core M CPU |
| | | Optimized-software implementation using AVX2: SHA-256(BYTE-only) 64 bit word size | 2582 | 2583 | 2584 | 2801 |
| RSA | PKCS1.5 | SIG(ver) Key sizes (modulus): 1024 bits, 2048 bits, 3072 bits Hash algorithms: SHA- 1, SHA-224, SHA-256, SHA-384, SHA-512 | 1704 | 1705 | 1706 | 1737 |
| ECDSA | FIPS 186-2 ANSI X9.62 | PKG: curves P-256, P-384 PKV: curves P-256, P-384 SIG(gen): curves P-256, P-384 SIG(ver): curves P-256, P-384 | 652 | 653 | 654 | 673 |
| HMAC | FIPS 198 | Generic-software implementation (non-optimized): KS <bs, ks="">BS HMAC-SHA-1 HMAC-SHA-224 HMAC-SHA-256 HMAC-SHA-384 HMAC-SHA-512 Key Size: at least 112 bits</bs,> | 2114 | 2115 | 2116 | 2159 |
| | | Optimized-software implementation using SSE: KS <bs, ks="">BS HMAC-SHA-1 HMAC-SHA-224 HMAC-SHA-256 Key Size: at least 112 bits</bs,> | 1967 | 1929 | 1930 | 2158 |

| Cryptographic | Standards | Usage / Description | | Va | ıl. No. | |
|---------------|------------|---|-----------|-----------|-------------|------------------|
| Function | | | i5 CPU | i7 CPU | Xeon CPU | Core M CPU |
| | | Optimized-software implementation not using SSE: KS <bs, ks="">BS HMAC-SHA-1 HMAC-SHA-224 HMAC-SHA-256</bs,> | 1966 | 1927 | 1928 | 2157 |
| | | Key Size: 112 bits | | | | |
| | | Optimized-software implementation using AVX1: | 1960 | 1961 | 1962 | 2155 |
| | | KS <bs, ks="BS,<br">KS>BS HMAC-SHA-256</bs,> | | | | |
| | | 64 bit word size | | | | |
| | | Optimized-software | 1963 | 1964 | 1965 | 2156 |
| | | implementation using AVX2: | .000 | | 1000 | 2.00 |
| | | KS <bs, ks="BS,<br">KS>BS</bs,> | | | | |
| | | HMAC-SHA-256 | | | | |
| 077 5750 | 05.000.004 | 64 bit word size | | | | |
| CTR DRBG | SP 800-90A | Generic-software implementation of AES (non-optimized) AES with 128 bit key size | 769 | 770 | 771 | 806 |
| | | Optimized-software implementation of AES: AES with 128 bit key size | 598 | 599 | 609 | 816 |
| | | AES-NI hardware implementation AES with 128 bit key size | 600 | 601 | 602 | 805 |
| PBKDF | SP 800-132 | Password based key derivation according using HMAC with SHA- 1 or SHA-2 as pseudorandom function | | Vendo | r Affirmed | 1 |

Table 3: Approved Security Functions

CAVEAT: The module generates cryptographic keys whose strengths are modified by available entropy – 160-bits.

Non-Approved Security Functions:

| Cryptographic Function | Usage / Description | Caveat |
|------------------------|--|---------------|
| AES | Optimized-assembler implementation using AVX: | Non-compliant |
| | Encryption / Decryption | |
| | Block Chaining Mode: GCM | |
| | 64 bit word | |
| | Optimized-assembler implementation using SSE3: | Non-compliant |
| | Encryption / Decryption | |
| | Block Chaining Mode: GCM, CTR | |
| | 64 bit word | |
| DES | Encryption and decryption: key size 56 bit; Used for NFS support in the raccoon IPSec cipher suite as a last resort when AES and Triple-DES ciphers are not supported by the remote end. | Non-Approved |
| Triple-DES | Optimized-assembler implementation: | Non-compliant |
| | Encryption / Decryption | |
| | Block Chaining Mode: CTR | |
| Triple-DES | Encryption and Decryption: | Non-compliant |
| | One key and two key implementation | |
| ANSI X9.63 | Hash Based KDF | Non-Approved |
| RFC6637 | KDF | Non-compliant |
| SP800-108 | KDF | Non-Approved |
| | Modes: Counter, Feedback | |
| SP800-56C | KDF | Non-Approved |
| MD2 | Hashing | Non-Approved |
| | Digest size 128 bit | |

| Cryptographic Function | Usage / Description | Caveat |
|--|--|--|
| MD4 | Hashing Digest size 128 bit | Non-Approved |
| MD5 | Hashing Digest size 128 bit | Non-Approved |
| RIPEMD | Hashing Digest size 128, 160, 256, 320 bits | Non-Approved |
| Ed25519 | Key Agreement Sig(gen) Sig(ver) | Non-Approved |
| ECDSA | PKG: curves P-192, P-224, P-521 PKV: curves P-192, P-224, P-521 SIG(gen): curves P-192, P-224, P-521 SIG(ver): curves P-192, P-224, P-521 | Non-Approved |
| ECDSA | key generation for compact point representation of points | Non-Approved |
| Integrated Encryption Scheme on elliptic curves | Encryption/Decryption | Non-Approved |
| RSA FIPS186-2 | PKCS#1 v1.5 SIG(ver) Key sizes (modulus): 1536 bits, 4092 bits Hash algorithms: SHA-1, SHA-224, SHA-256, SHA-384, SHA-512 | Non-compliant |
| RSA OAEP | Encryption and Decryption | Non-Approved, but allowed: RSA (key wrapping; key establishment methodology provides between 112 and 150 bits of encryption strength; non-compliant less than 112 bits of encryption strength) |
| AES KWP SP800-38F | Key Wrapping with 80 to 150 bits of security strength | Non-Approved AES (key wrapping; key establishment methodology provides between 128 and 160 bits of encryption strength). |
| CAST5 | Encryption and decryption: key sizes 40 to 128 bits in 8-bit increments | Non-Approved |

| Cryptographic Function | Usage / Description | Caveat |
|----------------------------|--|---------------|
| Blowfish | Encryption and decryption | Non-Approved |
| RC2 | Encryption and decryption: key size 8 to 1024 bits | Non-Approved |
| RC4 | Encryption and decryption: key size 8 to 1024 bits | Non-Approved |
| Hash-DRBG | Hash-DRBG using SHA1 derived from the SP800-90A without derivation function, without prediction resistance | Non-compliant |
| HMAC-DRBG | HMAC based RNG derived from SP800- 90A without prediction resistance | Non-compliant |
| CMAC AES128 | MAC generation | Non-Approved |
| OMAC (One- Key CBC MAC) | MAC generation | Non-Approved |

Table 4: Non-Approved Function

The encryption strengths included in Table 4 for the key establishment methods are determined in accordance with FIPS 140-2 Implementation Guidance [IG] section 7.5 and NIST Special Publication 800-57 (Part1) [SP800-57P1].

2.3 Cryptographic Module Boundary

The physical boundary of the module is the physical boundary of the OS X device that contains the module. Consequently, the embodiment of the module is a multi-chip standalone cryptographic module.

The logical module boundary is depicted in the logical block diagram given in Figure 1.

Device Physical Boundary




Figure 1: Logical Block Diagram

2.4 Module Usage Considerations

A user of the module must consider the following requirements and restrictions when using the module:

- When using AES-GCM, the caller must use the module's DRBG to generate at least 96 bits of random data that is used for the IV of AES-GCM. The caller is permitted to add additional deterministic data to that IV value in accordance with SP800-38D section 8.2.2. Users should consult SP 800-38D, especially section 8, for all of the details and requirements of using AES-GCM mode.
- When using AES, the caller must obtain a reference to the cipher implementation via the functions of ccaes_[cbc|ecb|...]_[encrypt|decrypt]_mode.
- When using SHA, the caller must obtain a reference to the cipher implementation via the functions ccsha[1|224|256|384|512]_di.
- In case the module's power is lost and then restored, the key used for the AES GCM encryption/decryption shall be re-distributed

3 Cryptographic Module Ports and Interfaces

The underlying logical interfaces of the module are the C language Kernel Programming Interfaces (KPIs). In detail these interfaces are the following:

- Data input and data output are provided in the variables passed in the KPI and callable service invocations, generally through caller-supplied buffers. Hereafter, KPIs and callable services will be referred to as "KPI."
- Control inputs which control the mode of the module are provided through dedicated parameters, namely the kernel module plist whose information is supplied to the module by the kernel module loader.
- Status output is provided in return codes and through messages. Documentation for each KPI lists possible return codes. A complete list of all return codes returned by the C language KPIs within the module is provided in the header files and the KPI documentation. Messages are documented also in the KPI documentation.

The module is optimized for library use within the OS X kernel and does not contain any terminating assertions or exceptions. It is implemented as an OS X kernel extension. The dynamically loadable library is loaded into the OS X kernel and its cryptographic functions are made available to OS X Kernel services only. Any internal error detected by the module is reflected back to the caller with an appropriate return code. The calling OS X Kernel service must examine the return code and act accordingly. There are two notable exceptions: (i) ECDSA does not return a key if the pair-wise consistency test fails; (ii) the DRBG algorithm loops a few iterations internally if the continuous test fails, eventually recovering from the error or causing a shutdown if the problem persists.

The function executing FIPS 140-2 module self-tests does not return an error code but causes the system to panic if any self-test fails – see Section 9.

The module communicates error status synchronously through the use of documented return codes indicating the module's status. It is the responsibility of the caller to handle exceptional conditions in a FIPS 140-2 appropriate manner.

Caller-induced or internal errors do not reveal any sensitive material to callers.

Cryptographic bypass capability is not supported by the module.

4 Roles, Services and Authentication

This section defines the roles, services and authentication mechanisms and methods with respect to the applicable FIPS 140-2 requirements.

4.1 Roles

The module supports a single instance of the two authorized roles: the Crypto Officer and the User. No support is provided for multiple concurrent operators or a maintenance operator.

| Role | General Responsibilities and Services (details see below) |
|---------------------|---|
| User | Utilization of services of the module listed in sections 2.1 and 4.2 |
| Crypto Officer (CO) | Utilization of services of the module listed in sections 2.1 and 4.2. |

Table 5: Roles

4.2 Services

The module provides services to authorized operators of either the User or Crypto Officer roles according to the applicable FIPS 140-2 security requirements.

Table 6 contains the cryptographic functions employed by the module in the Approved Mode. For each available service it lists, the associated role, the Critical Security Parameters (CSPs) and cryptographic keys involved, and the type(s) of access to the CSPs and cryptographic keys.

CSPs contain security-related information (secret and private cryptographic keys, for example) whose disclosure or modification can compromise the main security objective of the module, namely the protection of sensitive information.

The access types are denoted as follows:

- R: the item is read or referenced by the service
- W: the item is written or updated by the service
- Z: the persistent item is zeroized by the service

| Service | ce Role | | CSPs & crypto | Access | |
|----------------------------|------------------|----|---------------|--------|--|
| | U S E R | CO | keys | Туре | |
| Triple-DES | Х | Х | Secret key | R | |
| Encryption | | | | | |
| Input: plaintext, IV, key | | | | | |
| Output: ciphertext | | | | | |
| Decryption | | | | | |
| Input: ciphertext, IV, key | | | | | |
| Output: plaintext | | | | | |

| Service | | es | CSPs & crypto | Access |
|---|---------|----|---------------|--------|
| | U S E R | CO | keys | Туре |
| AES | Х | Χ | Secret key | R |
| Encryption Input: plaintext, IV, key Output: ciphertext | | | | |
| Decryption Input: ciphertext, IV, key | | | | |
| Output: plaintext | V | Х | None | NI/A |
| Secure Hash Generation | Х | ۸ | None | N/A |
| Input: message Output: message digest | | | | |
| HMAC generation | Х | Х | Secret HMAC | R |
| Input: HMAC key, message | ^ | ^ | key | |
| Output: HMAC value of message | | | | |
| RSA signature verification | Χ | Χ | RSA key pair | R |
| <i>Input:</i> the module n, the public key e, | | | | W |
| the SHA algorithm (SHA-1/SHA -224/SHA-256/SHA-384/SHA- | | | | |
| 512), | | | | |
| a message m, | | | | |
| a signature for the message | | | | |
| Output: pass if the signature is valid, | | | | |
| fail if the signature is invalid | | | | |

| Service | Role | | CSPs & crypto | Access |
|---|------------------|----|--|-------------|
| | U S E R | CO | keys | Туре |
| Signature generation Input: message m, q, a, b, X _G , Y _G , n, the SHA algorithm (SHA -224/SHA-256/SHA-384/SHA-512) sender's private key d Output: signature of m as a pair of r and s Signature verification Input: received message m', | X | X | ECDSA key pair | R W |
| signature in form on r' and s' pair, q, a, b, X _G , Y _G , n, sender's public key Q, the SHA algorithm (SHA-1/SHA -224/SHA-256/SHA-384/SHA- 512) Output: pass if the signature is valid, fail if the signature is invalid | | | | |
| Random number generation Input: Entropy Input, Nonce, Personalization String Output: Returned Bits | X | X | Entropy input string, Nonce, V and K | R W Z |
| PBKDF Password-based key derivation Input: encrypted key and password Output: plaintext key or Input: plaintext key and password Output: encrypted data | X | X | Secret key, password | R W Z |
| AES key import Input: key Output: N/A | X | X | Secret key | R |

| Service | | les | CSPs & crypto | Access | |
|---|---------|-----|-------------------------|--------|--|
| | U S E R | CO | keys | Type | |
| Triple-DES key import | Χ | Χ | Secret key | R | |
| Input: key | | | | | |
| Output: N/A | | | | | |
| HMAC key import | Χ | Х | HMAC key | R | |
| Input: key | | | | | |
| Output: N/A | | | | | |
| Release all resources of symmetric crypto function context | Х | Х | AES/Triple-DES key | Z | |
| Input: context | | | | | |
| Output: N/A | | | | | |
| Release all resources of hash context | Χ | Х | HMAC key | Z | |
| Input: context | | | | | |
| Output: N/A | | | | | |
| Release all resources of asymmetric crypto function context | X | Х | Asymmetric keys (ECDSA) | Z | |
| Input: context | | | | | |
| Output: N/A | | | | | |
| Reboot | Χ | Χ | N/A | N/A | |
| Self-test | Х | Х | Software integrity key | R | |
| Show Status | Х | Х | None | N/A | |

Table 6: Approved and Allowed Services in Approved Mode

| Service | Roles | | Access Type |
|---|---------|---|-------------|
| | USER CO | | |
| | | | |
| AES encryption and decryption | Х | Χ | R |
| Modes: | | | |
| CCM, GCM, CTR, CBC | | | |
| Integrated Encryption Scheme on elliptic curves encryption and decryption | X | Х | R |
| DES encryption and decryption | X | Х | R |

| Service | Roles | | Access Type | |
|--|-------|----|-------------|--|
| | USER | СО | | |
| TDES encryption and decryption Mode: CTR | X | X | R | |
| TDES encryption and decryption with One- Key and Two-Key implementations | X | X | R | |
| CAST5 encryption and decryption | X | Х | R | |
| Blowfish encryption and decryption | X | Х | R | |
| RC4 encryption and decryption | X | Х | R | |
| RC2 encryption and decryption | X | Х | R | |
| MD2 Hash | X | Х | R W | |
| MD4 Hash | X | Х | R W | |
| MD5 Hash | X | Х | R W | |
| RIPEMD Hash | X | Х | R W | |
| SP800-38F Key Wrapping with AES Core | Х | Х | R | |
| RSA Key Wrapping with RSAES-OAEP | X | Х | R | |
| RSA PKCS1-v1_5 Signature Verification Key sizes: 1536 bits, 4096 bits | X | X | R W | |
| ECDSA Key Pair Generation for compact point representation of points | X | X | R W | |
| PKG: curves P-192, P-224, P-521 PKV: curves P-192, P-224, P-521 SIG(gen): curves P-192,P-224, P-521 SIG(ver): curves P-192,P-224 P-521 | X | X | R W | |

| Service | Roles | | Access Type |
|--|-------|----|-------------|
| | USER | СО | |
| | | | |
| Ed 25519 Key agreement, Signature | X | X | R |
| Generation, Signature Verification | | | W |
| SP800-56C Key Derivation Function | X | Х | R |
| | | | W |
| Hash based Key Derivation Function using | X | Х | R |
| ANSI X9.63 | | | W |
| SP800-108 Key Derivation Function | X | Х | R |
| Modes: Feedback, Counter | | | W |
| Key Derivation Function based on RFC6637 | X | Х | R |
| | | | W |
| CMAC AES 128 MAC Generation | X | Х | R |
| | | | W |
| OMAC MAC Generation | X | Х | R |
| | | | W |
| HMAC-DRGB Random Number Generation | X | Х | R |
| | | | W |
| Hash-DRBG Random Number Generation | X | Х | R |
| | | | W |

Table 6b: Non-Approved Services in Non-Approved Mode

4.3 Operator authentication

Within the constraints of FIPS 140-2 level 1, the module does not implement an authentication mechanism for operator authentication. The assumption of a role is implicit in the action taken.

The module relies upon the operating system for any operator authentication.

5 Physical Security

The Apple OS X CoreCrypto Kernel Module, v5.0 is intended to operate on a multi-chip standalone platform. The device is comprised of production grade components and a production grade enclosure.

6 Operational Environment

The following sections describe the operational environment of the Apple OS X CoreCrypto Kernel Module, v5.0.

6.1 Applicability

The Apple OS X CoreCrypto Kernel Module, v5.0 operates in a modifiable operational environment per FIPS 140-2 level 1 specifications. The module is included in OS X 10.10, a commercially available general-purpose operating system executing on the hardware specified in section 2.1.3.

6.2 Policy

The operating system is restricted to a single-user mode of operation of the module (single-user mode; concurrent operators are explicitly excluded).

FIPS Self-Test functionality is invoked along with mandatory FIPS 140-2 tests when the module is loaded into memory by the operating system.

7 Cryptographic Key Management

The following section defines the key management features available through the Apple OS X CoreCrypto Kernel Module, v5.0.

7.1 Random Number Generation

The module uses a FIPS 140-2 approved deterministic random bit generator (DRBG) based on a block cipher as specified in NIST SP 800-90A. It is a CTR_DRBG with derivation function and without prediction resistance. Seeding is obtained by read_random (a true random number generator). read_random obtains entropy from interrupts generated by the devices and sensors attached to the system and maintains an entropy pool. The TRNG feeds entropy from the pool into the DRBG on demand. The TRNG provides 160-bits of entropy.

7.2 Key / CSP Generation

The following approved key generation methods are used by the module:

- The Approved DRBG specified in section 7.1 is used to generate cryptographic secret keys for symmetric key algorithms (AES, Triple-DES) and message authentication (HMAC).
- The Approved DRBG specified in section 7.1 is used to generate asymmetric key pairs for the ECDSA algorithm.

The module does not output any information or intermediate results during the key generation process. The DRBG itself is single-threaded.

The cryptographic strength of the 192 and 256 bit AES keys as well as the ECDSA keys for the curve P-384, as modified by the available entropy, is limited to 160-bits.

7.3 Key / CSP Establishment

The module provides key establishment services in the Approved Mode through the PBKDFv2 algorithm. The PBKDFv2 function is provided as a service and returns the key derived from the provided password to the caller. The caller shall observe all requirements and should consider all recommendations specified in SP800-132 with respect to the strength of the generated key, including the quality of the password, the quality of the salt as well as the number of iterations. The implementation of the PBKDFv2 function requires the user to provide this information.

7.4 Key / CSP Entry and Output

All keys are imported from, or output to, the invoking kernel service running on the same device. All keys entered into the module are electronically entered in plain text form. Keys are output from the module in plain text form if required by the calling kernel service. The same holds for the CSPs.

7.5 Key / CSP Storage

The Apple OS X CoreCrypto Kernel Module, v5.0 considers all keys in memory to be ephemeral. They are received for use or generated by the module only at the command of the calling kernel service. The same holds for CSPs.

The module protects all keys, secret or private, and CSPs through the memory protection mechanisms provided by OS X, including the separation between the kernel and user-space. No process can read the memory of another process. No user-space application can read the kernel memory.

7.6 Key / CSP Zeroization

Keys and CSPs are zeroized when the appropriate context object is destroyed or when the system is powered down.

8 Electromagnetic Interference/Electromagnetic Compatibility (EMI/EMC)

The EMI/EMC properties of the CoreCrypto KEXT are not meaningful for the software library. The devices containing the software components of the module have their own overall EMI/EMC rating. The validation test environments have FCC, part 15, Class B rating.

9 Self-Tests

FIPS 140-2 requires that the module performs self-tests to ensure the integrity of the module and the correctness of the cryptographic functionality at start up. In addition, the DRBG requires continuous verification. The FIPS Self-Tests functionality runs all required module self-tests. This functionality is invoked by the OS X Kernel startup process upon device initialization. If the self-tests succeed, the CoreCrypto KEXT instance is maintained in the memory of the OS X Kernel on the device and made available to each calling kernel service without reloading. All self-tests performed by the module are listed and described in this section.

9.1 Power-Up Tests

The following tests are performed each time the Apple OS X CoreCrypto Kernel Module, v5.0 starts and must be completed successfully for the module to operate in the FIPS approved mode. If any of the following tests fails the system shuts down automatically. To run the self-tests on demand, the user may reboot the system.

9.1.1 Cryptographic Algorithm Tests

| Algorithm | Modes | Test |
|--|--------------------|---|
| Triple-DES | CBC | KAT (Known Answer Test) |
| | | Separate encryption / decryption operations are performed |
| AES implementations selected by the | ECB, CBC | KAT |
| module for the corresponding environment | | Separate encryption / decryption operations are performed |
| AES-128, AES-192, AES-256 | | |
| DRBG | N/A | KAT |
| SHA implementations selected by the module for the corresponding environment | N/A | KAT |
| SHA-1, SHA-224, SHA-256, SHA-384, SHA-512 | | |
| HMAC-SHA-1, HMAC-SHA-224, HMAC-SHA-256, HMAC-SHA-384, HMAC-SHA-512 | N/A | KAT |
| ECDSA | SIG(ver), SIG(gen) | KAT, pair-wise consistency test |
| RSA | SIG(ver) | KAT |

Table 7: Cryptographic Algorithm Tests

9.1.2 Software / Firmware Integrity Tests

A software integrity test is performed on the runtime image of the Apple OS X CoreCrypto Kernel Module, v5.0. The CoreCrypto's HMAC-SHA-256 is used as an approved algorithm for the integrity test. If the test fails, then the system shuts down automatically.

9.1.3 Critical Function Tests

No other critical function test is performed on power up.

9.2 Conditional Tests

The following sections describe the conditional tests supported by the Apple OS X CoreCrypto Kernel Module, v5.0.

9.2.1 Continuous Random Number Generator Test

The Apple OS X CoreCrypto Kernel Module, v5.0 performs a continuous random number generator test, whenever CTR DRBG is invoked.

In addition, the seed source implemented in the operating system kernel also performs a continuous self-test.

9.2.2 Pair-wise Consistency Test

The Apple OS X CoreCrypto Kernel Module, v5.0 generates asymmetric keys and performs all required pair-wise consistency tests (signature generation and verification) with the newly generated key pairs.

9.2.3 SP 800-90A Assurance Tests

The Apple OS X CoreCrypto Kernel Module, v5.0 performs a subset of the assurance tests as specified in section 11 of SP 800-90A, in particular it complies with the mandatory documentation requirements and performs know-answer tests and prediction resistance.

9.2.4 Critical Function Test

No other critical function test is performed conditionally.

10 Design Assurance

10.1 Configuration Management

Apple manages and records source code and associated documentation files by using the revision control system called "Git".

Apple module hardware data, which includes descriptions, parts data, part types, bills of materials, manufacturers, changes, history, and documentation are managed and recorded. Additionally, configuration management is provided for the module's FIPS documentation.

The following naming/numbering convention for documentation is applied.

<evaluation>_<module>_<os>_<doc name>_<doc version (##.##)>

Example: FIPS_CORECRYPTO_OSX_KS_SECPOL_01.01

Document management utilities provide access control, versioning, and logging. Access to the Git repository (source tree) is granted or denied by the server administrator in accordance with company and team policy.

10.2 Delivery and Operation

The CoreCrypto KEXT is built into OS X 10.10. For additional assurance, it is digitally signed. The Approved Mode is configured by default and cannot be changed by a user.

10.3 Development

The Apple crypto module (like any other Apple software) undergoes frequent builds utilizing a "train" philosophy. Source code is submitted to the Build and Integration group (B & I). B & I builds, integrates and does basic sanity checking on the operating systems and apps that they produce. Copies of older versions are archived offsite in underground granite vaults.

10.4 Guidance

The following guidance items are to be used for assistance in maintaining the module's validated status while in use.

10.4.1 Cryptographic Officer Guidance

The Approved Mode of operation is configured in the system by default and cannot be changed. If the device starts up successfully then CoreCrypto KEXT has passed all self-tests and is operating in the Approved Mode.

10.4.2 User Guidance

The Approved Mode of operation is configured in the system by default. If the device starts up successfully then CoreCrypto KEXT has passed all self-tests and is operating in the Approved Mode.

Kernel programmers that use the module API shall not attempt to invoke any API call directly and only adhere to defined interfaces through the kernel framework.

11 Mitigation of Other Attacks

The module protects against the utilization of known Triple-DES weak keys. The following keys are not permitted:

```
{0xFE,0xFE,0xFE,0xFE,0xFE,0xFE,0xFE,0xFE},
\{0x1F,0x1F,0x1F,0x1F,0x0E,0x0E,0x0E,0x0E\}
\{0xE0,0xE0,0xE0,0xE0,0xF1,0xF1,0xF1,0xF1\}
\{0x01,0xFE,0x01,0xFE,0x01,0xFE,0x01,0xFE\},
{0xFE,0x01,0xFE,0x01,0xFE,0x01,0xFE,0x01},
\{0x1F,0xE0,0x1F,0xE0,0x0E,0xF1,0x0E,0xF1\},
\{0xE0,0x1F,0xE0,0x1F,0xF1,0x0E,0xF1,0x0E\},
\{0x01,0xE0,0x01,0xE0,0x01,0xF1,0x01,0xF1\},
\{0xE0,0x01,0xE0,0x01,0xF1,0x01,0xF1,0x01\},
\{0x1F,0xFE,0x1F,0xFE,0x0E,0xFE,0x0E,0xFE\},
\{0xFE,0x1F,0xFE,0x1F,0xFE,0x0E,0xFE,0x0E\},
\{0x01,0x1F,0x01,0x1F,0x01,0x0E,0x01,0x0E\},
\{0x1F,0x01,0x1F,0x01,0x0E,0x01,0x0E,0x01\},
{0xE0,0xFE,0xE0,0xFE,0xF1,0xFE,0xF1,0xFE}.
\{0xFE,0xE0,0xFE,0xE0,0xFE,0xF1,0xFE,0xF1\}.
```